

ANGLED 3030 CHANNEL

NOVA FLEX





Beam Angle
120°



Beam Angle
120°

Physical

Material	Anodized Aluminum
Length	2M**
Channel Options [Light Loss]	Silver [10%] Black [20%] White [0%]
Lens Options [Light Transmission]	Clear [92%] Soft [78%] Black [25%]


Lenses are suitable for outdoor use with respect to exposure to ultraviolet light and water exposure in accordance with UL 746C.

Every 2M of channel comes with 4 mounting clips and 2 end caps, one with a hole and one solid.

Product Codes for Ordering

Channel	Silver: NF-CH-3030-2M Black: NF/SP-CH-3030-2M-BK* White: NF/SP-CH-3030-2M-WT*
Round Lens	Clear: NF-CH-3030-C/CLEAR/CR-2M Soft: NF-CH-3030-C/SOFT/CR-2M Black: NF/SP-CH-3030-C/BLACK/CR-2M*
Square Lens	Clear: NF/SP-CH-3030-C/CLEAR/SQ-2M* Soft: NF-CH-3030-C/SOFT/SQ-2M Black: NF/SP-CH-3030-C/BLACK/SQ-2M*


Mounting Options



Direct Mount




Mount with Clips
NF-CH-3030-CLIP





Adjustable Clip
Angles: 0°/15°/30°/45°/60°/75°/90°
NF-CH-UNV-CLIP/ADJ



Dotting & Compatibility

LEDs	DS64	DS128	DS160	DS240	H2128	PRO60	PRO120	PRO240	ADJ160	RGB60	RGBW60	DRGB48
IP65	1	0	0	0	0	1	0	0	0	1	1	1
IP68	1	0	0	0	0	1	0	0	0	1	1	1



*Special Order Product Notes:
Lead-time 7-9 weeks
MOQ 150 pcs (2M/pc)

FOR MORE INFORMATION CLICK HERE

PROJECT SUPPORT | INSTALL GUIDE | WHY NOVA FLEX

**Custom length available, additional fee may apply.